

# E-MAPT ВАШ ПОСТАВЩИК DAHUA

https://emart.su/brands/dahua/

Федеральный Санкт-петербург 8 812 426-99-66 Москва Краснодар

8 800 511-77-41 8 495 137-99-67 8 861 205-62-66

www.emart.su

mail@emart.su



# DHI-NVR4416-16P-I

### 16Channel 1.5U 16PoE WizSense Network Video Recorder





Launched by Dahua Technology, WizSense is a series of AI products and solutions that adopt independent AI chip and deep learning algorithm. It focuses on human and vehicle with high accuracy, enabling users to fast act on defined targets. Based on Dahua's advanced technologies, WizSense provides intelligent, simple and inclusive products and solutions.

#### **System Overview**

Dahua new NVR4000-I network video recorder delivers excellent performance and high recording quality that is ideally suitable for IP video surveillance applications. This NVR adopts powerful processor, providing the capability of 4K resolution processing for applications where image details are highly required. Besides, the NVR supports input, recording and transmission functions. Additionally, the NVR can be served as edge storage, central storage or backup storage with an intuitive shortcut operation menu for remote management and control.

With build-in deep learning module, NVR4000-I series products adopt video image structuring technology based on deep learning algorithms, achieving high-precision human face recognition and perimeter protection. By applying deep learning artificial intelligence, NVR4000-I allows users to focus on what matters most, improves event response time and helps make video actionable.

The NVR is compatible with numerous third-party devices, which make it the perfect solution for surveillance systems that work independently of video management system (VMS).

#### **Functions**

#### **Perimeter Protection**

Automatically filtering out false alarms caused by animals, rustling leaves, bright lights, etc. Enables system to act secondary recognition for the targets. Improving alarm accuracy.

#### **Real Time Face Recognition**

Video stream & picture stream real time face recognition. Facial attributes analysis features including gender, age, expression, glasses, moustache, mouth mask. Identify people and also capture, record faces with metadata. Facial feature filtering while real time display, only show faces with target features.

- 16 Channel IP video access
- · Smart H.265+/H.265/Smart H.264+/H.264/MJPEG
- Up to 4 Channel perimeter protection
- Up to 2 Channel video stream face recognition/8 channel picture stream face recognition (with FD camera)
- Up to 12 face pictures/sec processing
- Up to 10 face databases with 20,000 face images in total
- 1-8 PoE Ports support ePoE & EoC



#### **Face Database Management**

Configurable multiple face databases. Powerful face database management. Face database can be applied to video channels independently. Name, gender, birthday, address, certificate type, certificate No., countries&regions and state can be added to each face picture.

#### Common/Stranger Mode

NVR4000-I supports common and stranger mode. In stranger mode, when NVR detects a strange face (not in device's face database), it can trigger alarm, buzzer, snapshot, record, etc. Similarity threshold can be set manually. This function is developed for important infrastructure sites for which access control is critical.

#### AI Search


Support seach by metadata of human and vehicles. Support uploading face pictures to NVR and compare them with recorded faces in NVR by similarity. Enable operators to quickly and easily search through multi channels and long duration, efficiently find out when and where a person of interest appeard.

#### ANPR

Automatic Number Plate Recognition available for convenient entrance/ exit management. Support license plate recognition (working with Dahua ITC camera), black/white list import/export, add/delete B/W list number, search result from recorded video.




Technical Specification		Alarm Output	4 Channel	
System		Playback and Backup		
Main Processor	Multi-core embedded processor	Sync Playback	1/4/9/16	
Operating System	Embedded LINUX	Search Mode	Time/Date, Alarm, MD and Exact Search (accurate to second)	
Perimeter Protection		Backup Mode	USB Device/Network	
Performance	4 channel, 10 IVS rules for each channel	Third-party Support	t	
Object classification	Human/Vehicle secondary recognition for tripwire and intrusion	Third-party Support	Arecont Vision, Airlive, AXIS, Canon, Dynacolor, JVC, LG, Panasonic, Pelco, Xunmei, Samsung, Sanyo, Sony,	
Al Search	Search by target classification (Human, Vehicle)	N	Watchnet and more	
Face Recognition			Network	
	Max 12 face pictures/sec processing	Interface	1 RJ-45 Port (10/100/1000 Mbps)	
Performance	2 channel video stream face recognition/8 channel picture stream face recognition (with FD camera)	PoE	16 ports (IEEE802.3af/at) 1-8 ports support ePoE & EoC	
Stranger Mode	Detect strangers' faces (not in device's face database). Similarity threshold can be set manually.  Up to 8 target face images search at same time, similarity	Network Function	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPP0E, DDNS, FTP, Alarm Center, IP Search (Support Dahua IP camera, DVR, NVS, etc.), P2P	
Al Search	threshold can be set for each target face image.	Max. User Access	128 users	
Database Management	Up to 10 face databases with 20,000 face images in total. Name, gender, birthday, address, certificate type, certificate No., countries&regions and state can be added to each face picture.	Mobile App	iPhone, iPad, Android	
		Interoperability	ONVIF (Profile S), SDK, CGI	
Database Application	Each database can be applied to video channels independently.	Storage	orvir (Fronce 3), 35K, edi	
Trigger Events	Buzzer, Voice Prompts, Email, Snapshot, Recording, Alarm Out, PTZ Activation, etc.	Internal HDD	4 SATA III Ports, Up to 8 TB capacity for each HDD	
Audio and Video		eSATA	NA	
IP Camera Input	16 Channel	Auxiliary Interface		
Two-way Talk	1 Channel Input, 1 Channel Output, RCA	USB	2 USB Ports (1 Rear USB 3.0 , 1 Front USB 2.0)	
Display		RS232	1 Port, for PC Communication and Keyboard	
Interface	1 HDMI, 1 VGA	RS485	1 Port, for PTZ Control	
	HDMI: 3840 × 2160, 1920 × 1080, 1280 × 1024, 1280 ×	Electrical		
Resolution	720 VGA: 1920 × 1080, 1280 × 1024, 1280 × 720	Power Supply	Single, AC100-240V, 4A	
Decoding Capability	2-ch@8MP (30fps), 8-ch@1080P (30fps)		NVR: <8.2W (Without HDD)	
Multi-screen Display	1/4/8/9/16	Power Consumption	PoE: Max 25.5W for single port 150W total rated power	
Recording		Environmental		
Bandwidth	200 Mbps (80 Mbps when AI function enabled, based on Dahua private protocol)	Operating Conditions	-10°C to +55°C (+14°F to +131°F), 86–106kpa	
Compression	Smart H.265+/H.265/Smart H.264+/H.264/MJPEG	Storage Conditions	0°C to +40°C (+32°F to +104°F), 30–85% RH	
Resolution	12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 1.3MP, 720P, D1 etc.	Construction		
Record Mode	Manual, Schedule (Continuous, MD (Motion Detection), Alarm, IVS)	Dimensions	1.5U, 440.0 mm × 411.1 mm × 76.0 mm (17.32" × 16.19" × 2.99")	
Record Interval	1–120 min (default: 60 min), Pre-record: 1–30 sec, Post-record: 10–300 sec	Net Weight	4.79 kg (10.6 lb) (without HDD)	
Video Detection and Alarm		Gross Weight 7.11 kg (15.7 lb) (without HDD)		
Trigger Events	Alarm Out, Video Push, Email, Recording, PTZ, Tour, Snapshot, Voice Prompt, Buzzer and Screen Tips	Certifications		
Video Detection	Motion Detection, MD Zones: 396 (22 × 18), Video Loss,	CE	EN55035, EN55032, EN55024, EN50130-4, EN60950-1	
	Tampering and Scene Change	FCC	Part 15 Subpart B, ANSI C63.4-2014	
Alarm Input	16 Channel			



Ordering Information			
Туре	Model	Description	
16 Channel WizSense NVR	DHI-NVR4416-16P-I	16 Channel 1.5U 16PoE WizSense Network Video Recorder	

# Dimensions (mm[inch])



## **Panels**

