



МАРТ

Е-МАРТ
ВАШ ПОСТАВЩИК
ДАГУА

<https://emart.su/brands/dahua/>

| | |
|-----------------|-----------------|
| Федеральный | 8 800 511-77-41 |
| Санкт-петербург | 8 812 426-99-66 |
| Москва | 8 495 137-99-67 |
| Краснодар | 8 861 205-62-66 |

www.emart.su

mail@emart.su

DH-PFS3106-4ET-60

4-Port PoE Switch (Unmanaged)



Product Overview

DH-PFS3106-4ET-60 is a layer two Hardened PoE Switch, which provides 4*10/100Mbps PoE ports, 1*100/1000 Mbps optical port and 1*10/100/1000Mbps Ethernet uplink port. With high level lightning protection and wide working temperature range makes it a better performance in outdoor or harsh environment.

Technical Specification

| | |
|------------------------|--|
| Model | DH-PFS3106-4ET-60 |
| Ethernet Port | 1*100/1000 Base-X 1*100/100/1000 Base-T 4*10/100 Base-T (PoE power supply) |
| PoE Power Consumption | Port1≤60W, Port2-4≤30W, Totals≤60W |
| PoE PIN Assignment | 1, 2, 4, 5 (V+), 3, 6, 7, 8 (V-) |
| PoE Power Management | Support |
| PoE Protocol | IEEE802.3af (PoE), IEEE802.3at (PoE+), Hi-PoE |
| Switching Capacity | 6.8G |
| Packet Forwarding Rate | 3.57Mpps |
| Packet Buffer Memory | 1Mb |
| MAC Table Size | 8K |
| Flow Control | Enable by default |
| Application Humidity | 5%~95% |
| Power | DC 48~57V power adapter |
| Lightning Protection | Common Mode 6KV Differential Mode 4KV |
| ESD Protection | Air Discharge 15KV Contact Discharge 8KV |
| Working Temperature | -30°C~65°C |
| Weight | 440g |
| Dimension(W×D×H) | 150mm×108mm×30mm |

Features

- Layer two Hardened PoE switch
- Supports PoE power management
- MAC auto learning and aging, MAC address capacity is 8K
- Conforms to IEEE802.3af and IEEE802.3at power supply standard. Port 1 supports Hi-PoE 60W power supply
- Supports IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards
- Wide working temperature design: -30°C~ 65°C
- Supports dual power backup

Accessories

| | |
|---------|--|
| Model | |
| PFT3900 | 155M 850nm,2km,LC, Multi-mode |
| PFT3950 | 1.25G 850nm,500m,LC, Multi-mode |
| PFT3910 | 155M 1310/1550nm,20km,LC, Single-mode |
| PFT3920 | 155M 1550/1310nm,20km,LC, Single-mode |
| PFT3960 | 1.25G 1310/1550nm,20km,LC, Single-mode |
| PFT3970 | 1.25G 1550/1310nm,20km,LC, Single-mode |