

E-MAPT ВАШ ПОСТАВЩИК ZKTECO

https://emart.su/brands/zkteco/

Федеральный Санкт-петербург 8 812 426-99-66 Москва Краснодар

8 800 511-77-41 8 495 137-99-67 8 861 205-62-66

www.emart.su

mail@emart.su



UHF RFID Standalone Terminal





U1000

U2000

U1000 and U2000 are long distance RFID access control machines which integrate functions of UHF readers and controllers. Compared with UHF readers, they increase access control functions and support TCP/IP communication, Wiegand in/out, two relays, 3rd party electric lock, door sensor, exit button, which enable easy installation and convenient use.

The machines also support ZKAccess 3.5 and ZKBioSecurity 3.0 software. They have obtained IP66 protection level certification and is suitable for outdoor use. With outstanding long distance identification capability, the machines can be used in many applications including long distance fixed vehicle access management, long distance access control management and long distance pedestrian access management.

Features



Long Reading Distance



IP66 Protect Level



Supports ZKAccess3.5& ZKBioSecurity3.0 software



Access Control Function

Applications



Long distance fixed vehicle management



Long distance access control management



Long distance pedestrian access management

Specifications

| Model | U1000E, U1000F | U2000E, U2000F |
|--------------------------|--|---------------------------|
| Card Capacity | 5000 cards | |
| Transactions | 30,000 | |
| Hardware Platform | ZMM220 | |
| Working Frequency | F Series: 902Mhz-928MHz; E Series: 865MHz-868MHz | |
| Reading Distance | 0 - 6m (Stable is 0 - 5m) | 0 -12m (Stable is 0 -10m) |
| Communication | TCP/IP (connect access software) , USB (connect demo) | |
| Access Control Interface | 3rd Party Electric Lock, Door Sensor, Exit Button, Alarm, Wiegand In/Out | |
| Access Control Functions | Standard access functions, anti-passback | |
| Antenna Gain | 8dBi | 12dBi |
| Output Power | 18dBm-26dBm | |
| Support Software | ZKAccess3.5, ZKBioSecurity3.0 | |
| Power Supply | DC12V, 3A | |
| Working Temperature | -20°C-+60°C | |
| Working Humidity | <95% (25°C) | |
| Dimension | 250mm*250mm*70mm (±5) | 445mm*445mm*70mm (±5) |

Accessory Products



PB Series Automatic Barrier

Wiegand Reader







Exit Button

Electric Lock

Alarm

Configuration





